


MORE THAN
20 YEARS
OF EXPERIENCE



FIRE ALARM DEVICES



POLISH
MANUFACTURER

W2 FIRE ALARM DEVICES

The main task of fire alarm devices is to emit signals about a fire risk and to warn building users about the possible danger. Signaling can be performed in the form of acoustic and optical signals. In order to increase the alarm efficiency, voice signaling devices (with voice messages) can also be used. The signaling devices produced by W2 have Certificates of Constancy of Performance and Certificates of Approval issued by CNBOP-PIB.



SAOZ-PK2

**SOUNDER WITH
VISUAL ALARM DEVICE,
OUTDOOR
(COMPLIANT WITH
EN 54-3, EN 54-23)**

MAIN FEATURES:

Sound output >110 dB @ 1m

4 sound patterns

Current consumption
<100 mA (24 V DC)

Synchronization option (acoustic
and optical part)

Volume adjustment (two-stage,
microswitch)

Available in 3 varieties: red light,
white light, red and white light
alternately

COOPERATING PRODUCTS:



PIP-3AN/0,75A



WSD-1



* SGO-Pgz3

**VOICE SOUNDER WITH
VISUAL ALARM DEVICE,
OUTDOOR
(COMPLIANT WITH
EN 54-3, EN 54-23)**

MAIN FEATURES:

Sound output >100 dB @ 1m

18 sound patterns

3 voice messages in 3 languages
(PL, EN, DE) each

Current consumption
<1100 mA (24 V DC)

Volume adjustment (potentiometer)

Synchronization option (acoustic
and optical part)

Available in 3 varieties:
SGO-Pgz3, SGO-Pgz3/śb,
SGO-Pgz3/śbcz

COOPERATING PRODUCTS:



PIP-3AN/1,25A



WSD-1

* You can upload any
voice messages
for SG-Pgw3, SGO-Pgw,
SGO-Pgz3





SO-P8

**VISUAL ALARM DEVICE,
OUTDOOR
(COMPLIANT WITH
EN 54-23)**

MAIN FEATURES:

Current consumption <30 mA (for default settings)

Synchronization option

Possibility to choose 1 of 4 optical shapes
(3m, 6m, 9m, 12m) in one device

Possibility to choose 1 of 4 flash frequencies
(0,5 Hz, 0,93 Hz, 1,12 Hz, 1,3 Hz) in one device

Possibility of using the "wave mode"

Reinforced housing IK07

Inrush current limiter

Available in 6 varieties: SO-P8/CC, SO-P8/CB,
SO-P8/CM, SO-P8/BC, SO-P8/BB, SO-P8/BM

COOPERATING PRODUCTS:



**PIP-1AN/O,375A
OR PIP-3AN/O,75A**



OM-2



OZ-50-2



SA-P8

**SOUNDER,
INDOOR
(COMPLIANT WITH
EN 54-3)**

MAIN FEATURES:

Sound output >100 dB @ 1m

16 sound patterns

Current consumption <40 mA (for default settings)

Synchronization option

Volume adjustment (potentiometer)

Gradual volume increasing option

Reinforced housing IK07

Inrush current limiter

Available in 2 varieties: SA-P8/C, SA-P8/B

COOPERATING PRODUCTS:



OM-1



WSD-1



**PIP-1AN/O,375A
OR PIP-3AN/O,75A**



OZ-50-3



SAO-P8

**SOUNDER WITH
VISUAL ALARM DEVICE,
INDOOR
(COMPLIANT WITH
EN 54-3, EN 54-23)**

MAIN FEATURES:

Sound output >100 dB @ 1m

16 sound patterns

Current consumption <94 mA (for default settings)

Synchronization option (acoustic and optical part)

Volume adjustment (potentiometer)

Gradual volume increasing option

Possibility to choose 1 of 4 optical shapes
(3m, 6m, 9m, 12m) in one device

Reinforced housing IK07

Inrush current limiter

Available in 6 varieties: SAO-P8/CC, SAO-P8/CB,
SAO-P8/CM, SAO-P8/BC, SAO-P8/BB, SAO-P8/BM

COOPERATING PRODUCTS:



OM-1



WSD-1



**PIP-1AN/O,375A
OR PIP-3AN/O,75A**



OZ-50-3



SA-K5, SA-K6, SA-K7

**SOUNDER,
INDOOR
(COMPLIANT WITH
EN 54-3)**

MAIN FEATURES:

Sound output >100 dB @ 1m

4 sound patterns

Current consumption
<50 mA (24 V DC)

Activation indicator:
SA-K6 – one LED diode,
SA-K7 – several LED diodes

COOPERATING PRODUCTS:



OM-1



WSD-1



PIP-1AN/0,375A



OZ-40-2



* SG-Pgw3

**VOICE SOUNDER,
INDOOR
(COMPLIANT WITH EN 54-3)**

MAIN FEATURES:

Sound output >90 dB @ 1m

18 sound patterns

3 voice messages in 3 languages
(PL, EN, DE) each

Current consumption
<220 mA (24 V DC)

Synchronization option

Volume adjustment (potentiometer)

COOPERATING PRODUCTS:



OM-1



WSD-1



PIP-3AN/0,75A



OZ-40-2



* SGO-Pgw

**VOICE SOUNDER WITH
VISUAL ALARM DEVICE,
INDOOR
(COMPLIANT WITH
EN 54-3, EN 54-23)**

MAIN FEATURES:

Sound output >90 dB @ 1m

18 sound patterns

3 voice messages in 3 languages
(PL, EN, DE) each

Current consumption
<300 mA (24 V DC)

Synchronization option (acoustic
and optical part)

Volume adjustment (potentiometer)

Available in 4 varieties:
SGO-PgwA, SGO-PgwB,
SGO-PgwA/śb, SGO-PgwB/śb

COOPERATING PRODUCTS:



OM-1



WSD-1



PIP-3AN/0,75A



OZ-50-3



*** SO-Pd11**

OPTICAL,
INDOOR

MAIN FEATURES:

Current consumption
<60 mA (24 V DC)

4 lighting effects

Option to turn on continuous light

***device does not have
a CPR Certificate**

COOPERATING PRODUCTS:



PIP-3AN/0,75A



OZ-40-2



*** SO-Pd12**

OPTICAL,
INDOOR

MAIN FEATURES:

Current consumption
<150 mA (24 V DC)

15 lighting effects

Option to turn on continuous light

***device does not have
a CPR Certificate**


COOPERATING PRODUCTS:



PIP-3AN/0,75A



OZ-50-3



HEADQUARTERS



CONTACT

 www.w2.com.pl

 +48 52 522 32 38

 zamowienia@w2.com.pl

 Ceramiczna 1A street, 86-005 Kruszyn Krajeński, POLAND

